

CS650DT

Low Profile In-Ceiling, Coaxial, Infinite Baffle Loudspeaker with Easy Install Grille

The easy to install CS series speakers are a full range ceiling loudspeaker that incorporates high tech woofer materials with a butyl rubber surround and the Patent Pending state-of-the-art diffractionless dome Ferrofluid cooled tweeter. The Patent Pending pivoting tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot.

This revolutionary combination provides superior and more natural sound for both foreground and background applications.

The Infinite Baffle design makes it the ideal choice for typical applications in open-beam attic or enclosed ceilings.

For efficiency and consistency, the CS650DT and CS800DT series are timbre-matched to the CS series, FIT series, and WS series of speakers.

In addition, most of the CS speakers incorporate a 3-position equalization switch, one each for bass and treble to fine-tune the acoustics and allow for various room surfaces.

The speaker grille color is white and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations, unlike other grilles that use magnets to hold them on which must be made of steel that will rust. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant, and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 7/32" to 1 3/16".

Electrical connection, up to 12 gauge wire, is made by two gold plated constant tension spring-loaded terminals.

With our limited Lifetime warranty, you are assured years of superior, trouble-free operation.

Part Number	92095
Manual URL	www.currentaudio.com
Accessories	New Construction Bracket NC6CB Part #92026
	Volume Control ZL60S Part #92035
	Volume Control ZL45R Part# 92034
	SpeKap Part # 92069



SPECIFICATIONS

Driver with Butyl Rubber Surround	MetaPlex Composite
Tweeter, Dual 3/4", Diffraction-less Dome	Silk Ferrofluid Cooled
Frequency response	70Hz - 19.5kHz
Power handling	5 - 100 Watts
SPL @ 1 Watt/1 meter	88db
Impedance 8 ohm nominal	Fixed Crossovers
Diameter x Depth	9 5/8"(245mm) X 3 11/16"(94mm)
Retrofit Cutout Diameter	8 5/32" (207mm)

